

709.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® LGA 1151 Socket Core™ i3, i5, i7 & Pentium Processors
- INTEL® Q170 Express Chipset
- SO-DIMM DDR3L 1333/1066MHz \* 2 (Max 16GB)
- Giga LAN Port \* 8
- Support HDMI \* 1, GPIO \* 1 (optional)
- Support COM Port \* 1 (RJ-45 type)
- Support USB 2.0 Port \* 2, USB 3.0 Port \* 2
- Power Source ■ 1U 200W FLEX POWER, AC 90~240V input
- Applications ■ Networking, Surveillance

|                     |  |
|---------------------|--|
| • Product Dimension | • 430 (W) * 251 (D) * 43 (H) mm  |
| • Product Model     | • JBC150F592-Q170-B  |
| • MB Model & Size   | • JNF592-Q170 / MINI-ITX   |
| • BIOS              | • AMI 128MB SMT Flash ROM  |
| • CPU               | • Intel® LGA 1151 Socket Core i7/i5/i3/Pentium Processor   |
| • Memory            | • SO-DIMM DDR3L 1333/1066MHz * 2 (Max 16GB)  |
| • Storage           | • 2.5" SATA HDD * 2 (Support RAID-1) or 3.5" SATA HDD * 1  |
| • Expansion         | • Full size Mini-PCIE * 1<br>• SIM Card Slot * 1<br>• Support TPM (optional)   |
| • FAN               | • DC-12V / 4020 FAN * 3  |
| • Front I/O Port    | • Power LED * 1, HDD LED * 1<br>• PW-SW * 1, RESET SW * 1<br>• USB 2.0 * 2   |
| • Rear I/O Port     | • AC input * 1<br>• PW SW * 1 & RESET SW * 1<br>• Giga LAN * 8<br>• USB 3.0 * 2<br>• HDMI * 1, GPIO * 1 (optional)<br>• COM * 1 (RJ-45 type) |
| • Power Source      | • 1U 200W FLEX POWER<br>• AC 90~240V input   |
| • Accessory         | • AC Cable * 1, Screw Package * 1<br>• User Manual * 1, CD * 1   |
| • Packing           | • Net Weight ■ 4.2KG<br>• Gross Weight ■ 5KG<br>• Color Box Dimension ■ 560 (W) x 400 (D) x 380 (H) mm                                       |
| • Temperature       | • Operating Temperature : 0°C~50°C<br>• Storage Temperature : -10°C~70°C   |

|                 |                                |
|-----------------|--------------------------------|
| • Certification | • CE, FCC, RoHS, ErP           |
| • Applications  | • Networking<br>• Surveillance |