

999.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake/Kabylake U-series Processor (15W)
- 2 \* 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 32 GB
- 2 \* USB2.0, 6 \* USB3.0, 1 \* COM, 1 \* DP, 1 \* HDMI, 2 \* RJ45, 1 \* Line in, 1 \* Mic+Line out
- M/B Form Factor : UTX (117x112mm)
- DC-12V\_40W Adapter

|             |   |
|-------------|---|
| MB Model    | – JNU792C-7100 _Core i3 Processor<br>– JNU792V-3865 UTX _Celeron Processor  |
| Part No.    | – COM series: HBFCU792C-7100-B / HBFCU792CW-7100-B<br>– TPM2.0 series: HBFCU792C-7100-T / HBFCU792CW-7100-T<br>– VGA series: HBFCU792V-3865-B / HBFCU792VW-3865-B                       |
| BIOS        | – AMI 16MB SMT Flash ROM  |
| CPU/Chipset | – Intel® Skylake/Kabylake U-series Processor (MAX : TDP 15W)<br>Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload. |
| Memory      | – 2 * 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 32 GB  |
| Storage     | – 1 * 2.5" SATA3 6Gb/s internal drive bay<br>– 1 * Full-size mSATA/mini-PCI Express shared slot   |

|                 |   |
|-----------------|---|
| Network         | <ul style="list-style-type: none"> <li>- 1 * Intel i211AT Gigabit LAN, 1 * Intel i219LM Gigabit LAN</li> <li>- 1 * Half-size mini-PCIE slot (for WIFI model installed)</li> </ul>   |
| Rear Panel I/O  | <ul style="list-style-type: none"> <li>- 4 * USB 3.0 ports / HBFCU792C-XXXX-B only</li> <li>- 2 * USB 3.0 ports , 2 * USB 2.0 / HBFCU792V-XXXX-B only</li> <li>- 1 * HDMI 1.4 (max. 4096 x 2304@24Hz resolution)</li> <li>- 1 * DP (max. 4096 x 2304@60Hz resolution) / HBFCU792C-XXXX-B only</li> <li>- 2 * RJ45</li> <li>- 1 * Line-in, 1 * Mic+Line out (Realtek ALC662VD)</li> <li>- 2 * Antenna holes (WiFi only)</li> <li>- 1 * DC-In jack</li> </ul> |
| Front Panel I/O | <ul style="list-style-type: none"> <li>- 1 * Power button</li> <li>- 1 * Power LED , 1 * HDD LED</li> <li>- 2 * USB 2.0 , 2 * USB 3.0</li> <li>- 1 * COM (RS232/422/485) / HBFCU792C(W)-XXXX-B only</li> <li>- 1 * VGA / HBFCU792V(W)-XXXX-B only</li> </ul>  |
| Power Source    | <ul style="list-style-type: none"> <li>- FSP AC TO DC Adapter / DC12V_3.3A_40W</li> <li>- AC 90~240V input</li> </ul>   |
| Compliance      | <ul style="list-style-type: none"> <li>- CE, FCC, LVDS, RoHS, ErP Ready</li> </ul>  |
| Temperature     | <ul style="list-style-type: none"> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -10 ~ 70° C</li> </ul>  |
| Dimensions      | <ul style="list-style-type: none"> <li>- 144 (W) x 116.9 (D) x 65 (H) mm</li> </ul>   |
| Packing         | <ul style="list-style-type: none"> <li>- Net Weight: 1.8KG</li> <li>- Gross Weight: 2.8KG</li> <li>- Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm</li> </ul>   |
| OS Support      | <ul style="list-style-type: none"> <li>- 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux</li> </ul>   |
| Warranty        | <ul style="list-style-type: none"> <li>- 2 Year limited warranty</li> </ul>   |