



598.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® LGA1151 Socket Core i3,i5,i7 & Pentium Processors(max.65W)
- Support DDR4-2133Mhz, 2\* SO-DIMM slot, up to 32GB memory
- 2\* USB2.0, 4\* USB3.0, 1\* HDMI, 1\* DP, 2\* RJ45, 1\* MIC, 1\* Line in, 1\* Line out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

|                 |  |
|-----------------|--|
| MB Model        | – JNF693-H110 / Mini ITX<br>– JNF694L-4200 / Mini ITX  |
| Part No.        | – HBJC150F693-H110-B (non-WIFI)<br>– HBJC150F693W-H110-B (WIFI)  |
| BIOS            | – AMI 64MB SMT Flash ROMM  |
| CPU/Chipset     | – Intel® LGA1151 Socket Core i3,i5,i7 & Pentium Processors   |
| Memory          | – 2 * DDR4-2133 up to 32GB   |
| Storage         | – 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay<br>– 1 * M.2_SSD (M key-2242/2260)   |
| Network         | – 2 * Realtek® 8111H Gigabit LAN<br>– 1 * Full-size mini-PCIE slot ( 802.11 b/g/n + BT 4.0 installed in WIFI model / Optional )  |
| Rear Panel I/O  | – 4 * USB 3.0<br>– 1 * HDMI (Max Resolution : 3840x2160@24Hz)<br>– 1 * DP (Max Resolution : 4096x2304@60Hz)<br>– 2 * RJ45<br>– 1 * Mic, 1 * Line in, 1 * Line-out (Realtek ALC662)<br>– 4 * RS232<br>– 1 * AC-in |
| Front Panel I/O | – 1 * Power button, 1 * Reset button<br>– 1 * Power LED, 1 * HDD LED<br>– 2 * USB 2.0  |
| Power Source    | – 1U 200W FLEX POWER<br>– AC 90~240V input   |
| Compliance      | – CE, FCC, LVDS, RoHS  |
| Temperature     | – Operating Temperature: 0 ~ 50° C<br>– Storage Temperature: -10 ~ 70° C   |
| Dimensions      | – 430 (W) x 252 (D) x 44 (H) mm  |
| Packing         | – Net Weight: 3.5KG<br>– Gross Weight: 4.5KG<br>– Color Box dimension: 560 (W) * 400 (D) * 140 (H) mm  |
| OS Support      | – 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux  |

|          |                           |
|----------|---------------------------|
| Warranty | - 2 Year limited warranty |
|----------|---------------------------|