

189.95 EUR
incl. 19% VAT, plus [shipping](#)



- Rockchip® A53 RK3328 Quad-core 1.5GHz
- Onboard 1333 /2GB DDR3L DRAM Max. 4GB
- 8G Flash ROM Max 32GB
- HBJC923R3328DG2NS: Support 1* GbE and 1* USB3.0
- HBJC923R3328DG2NL: Support 1* GbE and 1* 10/100M LAN
- Support 1* Micro SD Socket (Max 64G)
- 2* USB2.0, 1* OTG/DC-in, 1* HDMI, 1* Line-out
- 5V DC-in

| | | |
|-------------|--|--|
| MB Model | – JR3328-DG2N (1.8" SBC) | – JR3328-DG2NL (1.8" SBC) |
| Part No | – HBJC923R3328DG2NS | – HBJC923R3328DG2NL |
| CPU/Chipset | – Rockchip® ARM Cortex A53 RK3328 Quad-core 1.5GHz SoC Processor | |
| Memory | – 2GB/1333MHz DDR3L (Max 4GB) | |
| Storage | – 8GB Flash (Max 32GB) | |
| Network | – 1 * Realtek RTL8211F-CG / 10/100/1000Mbps | – 1 * 10/100 Mbps internal FE PHY – 1 * Realtek RTL8211F-CG / 10/100/1000Mbps |

| | | |
|--------------|---|--|
| Rear I/O | <ul style="list-style-type: none"> - 1* RJ45 - 1* USB3.0 - 2* USB2.0 | <ul style="list-style-type: none"> - 2* RJ45 - 2* USB2.0 |
| Side I/O | <ul style="list-style-type: none"> - 1* HDMI (3840 x 2160@60Hz) - 1* OTG/5V DC-in - 1* Audio Line-out - 1* Micro SD card socket | |
| Power Source | <ul style="list-style-type: none"> - DC 5V-3.0A - AC 100~240V input | |
| Compliance | <ul style="list-style-type: none"> - RoHS, CE, FCC, CE-LVD | |
| Temperature | <ul style="list-style-type: none"> - Operating temperature: -10 ~ 60° C - Storage Temperature: -20 ~ 65° C | |
| Dimensions | <ul style="list-style-type: none"> - 94.4 (W) x 60.5 (D) x 33.6 (H) mm - With Shelf: 110.0 (W) x 111.1 (D) x 33.6 (H) mm | |
| OS Support | <ul style="list-style-type: none"> - Android 7.1 | |
| Warranty | <ul style="list-style-type: none"> - 1 Year limited warranty | |
| Life Cycle | <ul style="list-style-type: none"> - Till 2022 Q1 | |