



1498.00 EUR

incl. 19% VAT, plus [shipping](#)

- Ruggedized ! IP65 !
- Intel Pentium Quad Core !
- GPS, LTE, NFC, Barcode !
- Vehicle docking optional !



Support:  [Specifications](#) |  [Produkt guide](#)

- 11.6" Windows Tablet with 2K Resolution
- Extra Light (<900g)
- IP65
- MIL-STD-810G on 1.2M Drop Proof, S&V, High/Low Temperature
- Hot-Swappable Battery

- 4.2 hrs Battery Life with 19.53Whr Battery
- Honeywell Software Decode Scanner 1D/2D
- WiFi ac/a/b/g/n, GPS & LTE
- NFC Module
- HW TPM 2.0 FIPS 140-2 Level 2 Compliance
- Optional docking stations (stationary or vehicle mount)

	Size	11.6" TFT-LCD
DISPLAY	Max. Resolution	1920 x 1080
	Luminance (cd/m2)	500nits (Option: 300 nits)
	Glass Type	Gorilla Glass 3 and Direct Bonding
	TYPE	P-CAP
TOUCH SCREEN	Touch	10 finger capacitive multi-touchscreen supporting glove mode and rain mode

TABLET	Operating System	Windows® 10 IoT Enterprise 2016 LTSB Multi-Language (Option: Linux CentOS7)
	Processor	Intel Apollo Lake Pentium N4200 (Quad-Cores) 1.1GHz with turbo frequency to 2.5GHz, 2MB L2 Cache (4 Threads)
	Chipset	Intel SoC Integrated
	System RAM	LPDDR4 3733MHz 8GB (Option: 4GB)
	System ROM	M.2 SSD 64GB / (Option: 256GB++)
	Wireless	IEEE 802.11 ac/a/b/g/n (2.4GHz/5GHz)
	Bluetooth	BT V4.2
	LTE/GPS	GPS (UBX-G8020-KT) LTE CAT4 Sierra Module
	NFC	NFC Reader (NXP NPC300)
	Barcode Scanner	SW Decode: Honeywell Swift Decoder (1D/2D Support)
	Rear Camera	8MP Auto-Focus CMOS built-in module with Flash LED
	Sensor	Ambient Light Sensor, Gyro Sensor & G-sensor
	Ambient Light Sensor	Yes
	Speaker	2 x 0.8W
	Microphone	Yes
	LED Indicator	Charging LED, Power LED
	Main Battery	4.2 hr, 19.53Whr Removable lithium battery with latch lock (2570mAh, 7.6V)
	Hot-Swappable Battery	Yes, 2.66Whr back-up battery (700mAh*1, 3.8V, 1S1P)
	I/O Port	1 x USB 3.0 Type-A / 1 x Nano-SIM / 1 x Audio Jack / 1 x DC Jack / 1 x POGO Connector
	Keypad	2 x Volume Key
Fully Rugged Feature	IP65 / MIL-STD-810G 1.5m Drop / Shock & Vibration / Sand & Dust-Blowing Sand / High/Low Temperature – Operation / High/Low temperature – Storage / Freeze/thaw –Rapid temperature change / Thermal Shock	
	Dimension	299 x 199 x 17.7 mm (w/o bumpers & hand-strap) / 307.9 x 207.9 x 29.3 mm (w/ bumpers & hand-strap)
Weight	895g	
Operating Temperature	-10°C ~ 50°C	
Storage Temperature	-20°C ~ 60°C	
Storage Humidity	10% ~ 90% @40°C non-condensing	
Security	HW TPM 2.0 FIPS 140-2 Level 2 Compliance	
Certification	CE / FCC / VCCI	
Power Adapter	AC to DC, DC19V 65W Adaptor	
ACCESSORY	Hand-strap	Yes
	Shoulder-strap	Yes